



Specifiche Tecniche
(Technical Specifications)

DATA COF JOLLY



PORTATA CAPACITY		600 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		21 MIN
CONTROCORRENTE COUNTER CURRENT		1 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		12 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		5 MIN
LAVAGGIO VELOCE QUICK WASH		3 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		0,90 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		6 LT
CONTENUTO SALE SALT CONTENT		15 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		46,5 CM
LARGHEZZA WIDTH		24 CM
PROFONDITA' DEPTH		43,5 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	1550 LT
DUREZZA IN GRADI FRANCESI	30° F	1050 LT
HARDNESS IN FRENCH DEGREES	40° F	775 LT
	50° F	620 LT