

aqua service

THOMAS

Specifiche Tecniche
(Technical Specifications)

DATACOF MAXI



PORTATA CAPACITY		1400 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/4 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		51 MIN
CONTROCORRENTE COUNTER CURRENT		3 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		30 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		13 MIN
LAVAGGIO VELOCE QUICK WASH		5 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		2 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		16,5 LT
CONTENUTO SALE SALT CONTENT		70 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		101 CM
LARGHEZZA WIDTH		32 CM
PROFONDITA' DEPTH		52 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	3750 LT
DUREZZA IN GRADI FRANCESI	30° F	2500 LT
HARDNESS IN FRENCH DEGREES	40° F	1870 LT
	50° F	1500 LT