

aqua service

THOMAS

Specifiche Tecniche
(Technical Specifications)

DATA COF TOMMY



PORTATA CAPACITY		800 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		25 MIN
CONTROCORRENTE COUNTER CURRENT		1 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		15 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		6 MIN
LAVAGGIO VELOCE QUICK WASH		3 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		1,2 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		9 LT
CONTENUTO SALE SALT CONTENT		20 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		57 CM
LARGHEZZA WIDTH		24 CM
PROFONDITA' DEPTH		43.5 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	2100 LT
DUREZZA IN GRADI FRANCESI	30° F	1400 LT
HARDNESS IN FRENCH DEGREES	40° F	1050 LT
	50° F	850 LT