

aqua service

THOMAS

Specifiche Tecniche
(Technical Specifications)

DOMUS HW 12 DC



PORTATA MASSIMA MAX CAPACITY		1000 LT/H
PORTATA CONSIGLIATA RECOMMENDED CAPACITY		800 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		4°C - 70°C
RACCORDO IN- OUT IN-OUT FITTING		1" FEMMINA GAS
ALIMENTAZIONE ELETTRICA POWER SUPPLY		220 V 50 HZ
VALVOLA COMANDO VALVE MODEL		FLECK 4600 HW IN BRONZO
BOMBOLA TANK		ACCIAIO AISI 316 (28 LT) AISI 316 STAINLESS STEEL (28 LT)
CONTENUTO RESINA RESIN CONTENT		14 LT
CONTENUTO SALE SALT CONTENT		35 KG
MISURE INGOMBRI ADDOLCITORE SOFTENER MEASUREMENTS		
ALTEZZA HEIGHT		63 CM
LARGHEZZA WIDTH		20 CM
PROFONDITA' DEPTH		20 CM
MISURE INGOMBRI TINO SALE SALT CONTAINER MEASUREMENTS		
ALTEZZA HEIGHT		44 CM
DIAMETRO DIAMETER		31 CM
MODELLO CONTENITORE SALE SALT CONTAINER TYPE		FOOD SAFE - NON TOXIC
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	2000 LT
DUREZZA IN GRADI FRANCESI	30° F	1800 LT
HARDNESS IN FRENCH DEGREES	40° F	1300 LT
	50° F	1100 LT