



Specifiche Tecniche
(Technical Specifications)

ECO JOLLY



THOMAS		15-20	20-25	25-30	30-35	35-40	40-45	45-50
M³	1,40	1,20	1,00	0,82	0,68	0,55	0,45	0,35
Lt.	1400	1200	1000	820	680	550	450	350

JOLLY
8

LIVELLO MIN SALE

LIVELLO MAX SALE

PORTATA CAPACITY		600 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8"
RACCORDO SCARICO DRAIN FITTING		1/2"
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		37 MIN
PROGRAMMA PROGRAM		3
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		0,90 KG
VALVOLA COMANDO VALVE MODEL		AUTOTROL 368/604
PROGRAMMAZIONE SYSTEM		CRONO CHRONOMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		RACCORDO TROPPO PIENO OVERFLOW FITTING
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		6,2 LT
CONTENUTO SALE SALT CONTENT		15 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		42,5 CM
LARGHEZZA WIDTH		24 CM
PROFONDITA' DEPTH		48 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	1550 LT
DUREZZA IN GRADI FRANCESI	30° F	1050 LT
HARDNESS IN FRENCH DEGREES	40° F	775 LT
	50° F	620 LT