

aqua service



Specifiche Tecniche
(Technical Specifications)

HOME CAB GRANBAR



PORTATA CAPACITY		1000 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		37 MIN
CONTROCORRENTE COUNTER CURRENT		3 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		20 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		9 MIN
LAVAGGIO VELOCE QUICK WASH		5 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		1,7 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA ARGENTIZZATA SILVERED RESIN CONTENT		13 LT
CONTENUTO SALE SALT CONTENT		25 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		66 CM
LARGHEZZA WIDTH		32 CM
PROFONDITA' DEPTH		52 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	3250 LT
DUREZZA IN GRADI FRANCESI	30° F	2100LT
HARDNESS IN FRENCH DEGREES	40° F	1600 LT
	50° F	1300 LT