



Specifiche Tecniche
(Technical Specifications)

HOME CAB MINIBAR



PORTATA CAPACITY		400 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		17 MIN
CONTROCORRENTE COUNTER CURRENT		1 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		10 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		3 MIN
LAVAGGIO VELOCE QUICK WASH		3 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		0,45KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA ARGENTIZZATA SILVERED RESIN CONTENT		3,5 LT
CONTENUTO SALE SALT CONTENT		5 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		46,5 CM
LARGHEZZA WIDTH		19,5 CM
PROFONDITA' DEPTH		33 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	875 LT
DUREZZA IN GRADI FRANCESI	30° F	580 LT
HARDNESS IN FRENCH DEGREES	40° F	430 LT
	50° F	350 LT