

aqua service

THOMAS

Specifiche Tecniche
(Technical Specifications)

HOME CAB SUPERMAXI



PORTATA CAPACITY		2000 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/4 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		73 MIN
CONTROCORRENTE COUNTER CURRENT		5 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		40 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		20 MIN
LAVAGGIO VELOCE QUICK WASH		8 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		3,3 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA ARGENTIZZATA SILVERED RESIN CONTENT		25 LT
CONTENUTO SALE SALT CONTENT		60 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		101 CM
LARGHEZZA WIDTH		32 CM
PROFONDITA' DEPTH		52 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	6250 LT
DUREZZA IN GRADI FRANCESI	30° F	4150 LT
HARDNESS IN FRENCH DEGREES	40° F	3120 LT
	50° F	2500 LT