



Specifiche Tecniche
(Technical Specifications)

HOME CAB TOMMY



THOMAS		15-20	20-25	25-30	30-35	35-40	40-45	45-50
MP	2,20	1,50	1,30	1,10	1,00	0,85	0,80	
LL	2000	1600	1300	1100	1000	850	800	

LIVELLO MIN SALE

PORTATA CAPACITY		800 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		25 MIN
CONTROCORRENTE COUNTER CURRENT		1 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		15 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		6 MIN
LAVAGGIO VELOCE QUICK WASH		3 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		1,2 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F79-LCD
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA ARGENTIZZATA SILVERED RESIN CONTENT		9 LT
CONTENUTO SALE SALT CONTENT		20 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		57 CM
LARGHEZZA WIDTH		24 CM
PROFONDITA' DEPTH		43.5 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	2100 LT
DUREZZA IN GRADI FRANCESI	30° F	1400 LT
HARDNESS IN FRENCH DEGREES	40° F	1050 LT
	50° F	850 LT