

aqua service

THOMAS

Specifiche Tecniche
(Technical Specifications)

MOKA COMPACT



PORTATA CAPACITY		500 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		18 MIN
CONTROCORRENTE COUNTER CURRENT		1 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		10 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		4 MIN
LAVAGGIO VELOCE QUICK WASH		3 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		0,60 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F69P1
PROGRAMMAZIONE SYSTEM		CRONO CHRONOMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		NO
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		4,5 LT
CONTENUTO SALE SALT CONTENT		8 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		45,5 CM
LARGHEZZA WIDTH		22 CM
PROFONDITA' DEPTH		36,5 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	1125 LT
DUREZZA IN GRADI FRANCESI	30° F	750 LT
HARDNESS IN FRENCH DEGREES	40° F	560 LT
	50° F	450 LT