



Specifiche Tecniche
(Technical Specifications)

MOKA JOLLY



PORTATA CAPACITY		600 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		21 MIN
CONTROCORRENTE COUNTER CURRENT		1 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		12 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		5 MIN
LAVAGGIO VELOCE QUICK WASH		3 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		0,90 KG
VALVOLA COMANDO VALVE MODEL		RUNXIN F69P1
PROGRAMMAZIONE SYSTEM		CRONO CHRONOMETRIC
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		NO
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		6 LT
CONTENUTO SALE SALT CONTENT		15 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		45,5 CM
LARGHEZZA WIDTH		24 CM
PROFONDITA' DEPTH		43,5 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	1550 LT
DUREZZA IN GRADI FRANCESI	30° F	1050 LT
HARDNESS IN FRENCH DEGREES	40° F	775 LT
	50° F	620 LT