

aqua service

THOMAS

Specifiche Tecniche
(Technical Specifications)

HORELUX OVER



PORTATA CAPACITY		2000 LT/H
PRESSIONE MIN. MIN PRESSURE		1,5 ATE
PRESSIONE MAX. MAX PRESSURE		7 ATE
TEMPERATURA TEMPERATURE		2°C - 35°C
RACCORDO IN- OUT IN-OUT FITTING		3/8 "
RACCORDO SCARICO DRAIN FITTING		P. GOMMA ELBOW HOSE COUPLING
ALIMENTAZIONE POWER SUPPLY		12 V DC
DURATA RIGENERAZIONE REGENERATION TIME		85 MIN
CONTROCORRENTE COUNTER CURRENT		5 MIN
ASPIRAZIONE SALAMOIA BRINE SUCTION		50 MIN
RIPRISTINO SALAMOIA BRINE RESTORATION		22 MIN
LAVAGGIO VELOCE QUICK WASH		8 MIN
CONSUMO SALE PER RIGENERAZIONE SALT CONSUMPTION PER REGENERATION		3,9 KG
VALVOLA COMANDO VALVE MODEL		APEX GZ 2
PROGRAMMAZIONE SYSTEM		CRONO / VOLUME CHRONOMETRIC / VOLUMETRIC
AUTODISINFEZIONE (ATTIVAZIONE MANUALE) SELF-DISINFECTION (MANUAL ACTIVATION)		SI YES
FINE LAVAGGIO IN ASSENZA CORRENTE END OF WASH CYCLE IN THE ABSENCE OF POWER		SI YES
REGOLAZIONE MIX DUREZZA HARDNESS MIX ADJUSTMENT		SI YES
SISTEMA ANTIALLAGAMENTO OVERFLOW SYSTEM		SI YES
BOMBOLA TANK		POLIETILENE RINFORZATO IN FIBRA DI VETRO FIBERGLASS REINFORCED POLYETHYLENE
CONTENUTO RESINA RESIN CONTENT		30 LT
CONTENUTO SALE SALT CONTENT		60 KG
MISURE INGOMBRI MEASUREMENTS		
ALTEZZA HEIGHT		121 CM
LARGHEZZA WIDTH		32 CM
PROFONDITA' DEPTH		52 CM
ACQUA ADDOLCITA EROGATA IN BASE A: SOFTENED WATER SUPPLIED BASED ON		
	20° F	7500 LT
DUREZZA IN GRADI FRANCESI	30° F	5000 LT
HARDNESS IN FRENCH DEGREES	40° F	3750 LT
	50° F	3000 LT